



Tumaker BigFoot 500 Modular

INDEPENDENT AND INTERCHANGEABLE EXTRUDERS
PELLETS - DIRECT DRIVE HR

Includes **Simplify 3D** License

Tumaker

www.tumaker.com

info@tumaker.com

(+34) 943 943 855

	BigFoot 500 Modular (Direct Drive HR)	BigFoot 500 Modular (Pellet)	BigFoot 500 Modular Dual (Direct Drive HR - Direct Drive HR)	BigFoot 500 Modular Dual (Pellet - Direct Drive HR)	BigFoot 500 Modular Dual (Pellet - Pellet)
Number of Extruders	1 (Direct Drive HR)	1 (Pellets)	2 (Direct Drive HR - Direct Drive HR)	2 (Direct Drive HR - Pellets)	2 (Pellets - Pellets)
Compatible Nozzles	0.15 mm, 0.25 mm, 0.4 mm, 0.6 mm , 0.8 mm	0.4 mm, 0.6 mm, 0.8 mm, 2.0 mm, 4.0 mm, 5.0 mm	0.15 mm, 0.25 mm, 0.4 mm, 0.6 mm , 0.8 mm	Filament (mm): 0.15, 0.25, 0.4, 0.6, 0.8 Pellet (mm): 0.4, 0.6, 0.8, 2.0, 4.0, 5.0	0.4 mm, 0.6 mm, 0.8 mm, 2.0 mm, 4.0 mm, 5.0 mm
Included Nozzles	0.4 mm	0.8 mm	0.4 mm (2 pcs)	Filament: 0.4 mm Pellet: 0.8 mm	0.8 mm (2 pcs)
Materials	ABS, ASA, NYLON, PET-G, PLA, PP, TPU Hardness, TPU...	Recommended pellet size: Circular 3 - 5 mm	ABS, ASA, NYLON, PET-G, PLA, PP, TPU Hardness, TPU...	Pellets: Circular 3 - 5 mm Filaments: ABS, ASA, NYLON, PET-G, PLA, PP, TPU Hardness, TPU...	Recommended pellet size: Circular 3 - 5 mm
Print Volume	500 x 500 x 500 mm				
Printer Weight	92 kg				
Printer Dimensions	1040 x 835 x 1044 mm				
Heated Bed Temperature	Up to 100 °C				
Head Temperature	Up to 300 °C				
Calibration	Automatic				
Structure	Closed with filters				
Connectivity	Wi-Fi, Ethernet, Micro SD				
Noise Emission	44 dB (40 dB with door closed)				
Display	7" colour touch screen				
Compatible Software	MacOS, Windows, Linux				
Power	120W, 600W, 1350W				
Compatible Slicing Software	Simplify 3D, CURA, SuperSlicer				
File Format	STL, OBJ, Gcode				
Warranty	1 year				
Package Weight	160 kg				
Package Dimensions	1153 x 1000 x 1197 mm				