



Tumaker NX 300 Modular

CABEZALES INDEPENDIENTES E INTERCAMBIABLES
PELLETS - DIRECT DRIVE HR

Incluye licencia **Simplify 3D**



 www.tumaker.com
 info@tumaker.com
 (+34) 943 943 855

	NX 300 Modular (Direct Drive HR)	NX 300 Modular (Pellet)	NX 300 Modular Dual (Direct Drive HR - Direct Drive HR)	NX 300 Modular Dual (Pellet - Direct Drive HR)	NX 300 Modular Dual (Pellet - Pellet)
Número de cabezales	1 (Direct Drive HR)	1 (Pellets)	2 (Direct Drive HR - Direct Drive HR)	2 (Direct Drive HR - Pellets)	2 (Pellets - Pellets)
Boquillas compatibles	0.15 mm, 0.25 mm, 0.4 mm, 0.6 mm , 0.8 mm	0.4 mm, 0.6 mm, 0.8 mm, 2.0 mm, 4.0 mm, 5.0 mm	0.15 mm, 0.25 mm, 0.4 mm, 0.6 mm , 0.8 mm	Filament (mm): 0.15, 0.25, 0.4, 0.6, 0.8 Pellet (mm): 0.4, 0.6, 0.8, 2.0, 4.0, 5.0	0.4 mm, 0.6 mm, 0.8 mm, 2.0 mm, 4.0 mm, 5.0 mm
Boquillas incluidas	0.4 mm	0.8 mm	0.4 mm (2 uds)	Filamento: 0.4 mm Pellet: 0.8 mm	0.8 mm (2 uds)
Materiales	ABS, ASA, NYLON, PET-G, PLA, PP, TPU Hardness, TPU...	Tamaño recomendado: Circular de 3 a 5 mm	ABS, ASA, NYLON, PET-G, PLA, PP, TPU Hardness, TPU...	Pellets: Circular de 3 a 5 mm Filamentos: ABS, ASA, NYLON, PET-G, PLA, PP, TPU Hardness, TPU...	Tamaño recomendado: Circular de 3 a 5 mm
Área de Trabajo	300 x 300 x 250 mm				
Peso de la impresora	56 kg				
Dimensiones de la impresora	840 x 635 x 805 mm				
Temperatura de la cama caliente	Hasta 100 °C				
Temperatura del cabezal	Hasta 300 °C				
Calibración	Automática				
Estructura	Cerrada con filtros				
Conectividad	Wi-Fi, Ethernet, Micro SD				
Emisión de ruido	44 dB (40 dB con la puerta cerrada)				
Pantalla	7" táctil a color				
Software compatible	MacOS, Windows, Linux				
Nivel de potencia	120W, 600W, 1350W				
Software de corte compatible	Simplify 3D, CURA, SuperSlicer				
Formato de archivos	STL, OBJ, Gcode				
Garantía	1 año				
Peso del paquete	114 kg				
Dimensiones del paquete	953 x 800 x 957 mm				